

ABOUT COLOUR

paint & design

ABOUT COLOUR EASYSAND GIB SEALER

TYPICAL APPLICATION: Interior water based sealer for new gib board, MDF and customwood

PRODUCT FEATURES: Excellent adhesion to substrate
High filling and high build properties
Excellent levelling and easy sanding
About Colour Deep Base is available for use under dark or bright topcoats as the equivalent depth of colour can be achieved ensuring good coverage.

COLOUR: About Colour Easysand can be tinted toward light-mid tone colours.
About Colour Deep Base is available for use under dark or bright topcoats as the equivalent depth of colour can be achieved ensuring good coverage.

PRODUCT DESCRIPTION:

Appearance when dry: Dull flat finish
Pack size: 1,4,10 Litre Deep base 1, 4 Litre
Theoretical coverage: 10 - 12 sq metre per litre depending on surface profile and porosity
Storage temperature: Minimum 10°C, Maximum 50°C
Shelf life: 18 months
Wet film thickness per coat: Up to 500 microns.

INTERIOR CEILING APPLICATIONS:

Mixing: Stir well using a broad paddle. Check colour before use.

Gib board: Ensure stopping is completed to a high standard. Sand all surfaces with #150 grit or finer (#220) sand paper. Remove all dust etc. from walls and floors. Spray, roll or brush on a full coat. Allow to dry (overnight). Sand with flat faced sanding tool, #150-220 grit until surface defect free. Fill any minor defects with knifing compound (e.g. Rapid Filler), sand again and fill any defects if present. Do not expose paper of Gib Board. Note: The appearance should now be uniform in colour and appearance. Stopping should not be visible. Re-apply a light coat if stopping still visible then re-sand. To achieve a level 5 finish, the preferred method of application is spray, applying a thicker film with minimal surface texture.
Note: Spray applying the first coat as a "light" application followed up with a full coat when tack free, provides a good foundation to sand back on. This "wets out" the surface, minimizes substrate defects and ensures maximum adhesion for About Colour easysand.

**Interior blockwork/
concrete:**

About Colour Easysand is excellent for filling the pores and providing a good surface for finish coats.

Wood: Apply as for Gib Board. Staining can result from the sap of some timbers. About Colour Alkyd Sealer can be used to reduce this. For MDF etc, apply as Gib Board.

Application: Apply by brush, roller or spray. (Needs to be over coated).

Spray: Use airless spray (2500psi min), with tip 515/513 approx or larger. Film build can be in excess of 500 microns without sagging, per coat.

Roller: Use 6-10 mm nap, dacron roller or similar, applying full coat. Do not roll excessively as this will reduce film build and detract from the final quality of finish.

Brush: Use good quality brush. Apply a full coat.

Note: Sanding may be undertaken as soon as the About Colour Easy sand is dry, say 2-3 hours at 200 C. It may be left longer (overnight) and will sand easily.

Thinning & clean up: Can be thinned up to 10% for ease of application during hot weather. Clean up in water. Use a small amount of detergent to aid clean up.

APPLICATION DETAILS

Application temperature range: 10°C - 35°C Note: Do not apply when air or surface temperature is likely to fall below 10°C.

Maximum relative humidity: 75%

ENVIRONMENTAL:

The About Colour range of products are formulated on the latest available resins to give you both high performance and also to meet Low VOC (Volatile Organic Compound) levels set out in current local standards. Likewise levels of environmentally harmful substances are either significantly reduced or eliminated. DO NOT POUR paint or wash down storm water or water courses. ALWAYS dispose of in accordance with local Government regulations. Soak up spills with absorbent material and dispose of properly. If spraying use suitable respiratory protection.

HEALTH AND SAFETY

Special pre-cautions:

- + Keep out of reach of children.
- + This material is not to be taken internally.
- + Protect from freezing.
- + Avoid breathing vapour - use with adequate ventilation. Seal container after use.
- + Avoid contact with eyes and prolonged contact with skin.
- + Dispose of empty container carefully.
- + Do not dispose of paint in sewers or waterways.

FIRST AID

If swallowed:

Give water to dilute. Do not induce vomiting. Get medical attention.

Eye contact:

Flush with running water immediately for at least 15 minutes. Get medical attention.

This information is intended to give a fair description of the product and its capabilities under specific conditions and is correct at the time of printing. It does not constitute an offer by the manufacturers nor do they warrant or guarantee its accuracy of completeness in describing the performance or suitability of the product. The manufacturer's guarantee is only applicable to full About Colour systems and is limited to product replacement only and does not include surface preparation or application.

www.aboutcolour.co.nz