

# ABOUT COLOUR

p a i n t & d e s i g n

## ABOUT COLOUR MATT ACRYLIC

---

**TYPICAL APPLICATION:** A 100% acrylic based interior ultra low sheen paint. Specially formulated with ceramic pigments to give easy spray application with an excellent tough, durable, washable surface. 100% pure acrylic Matt for interior walls and ceilings.

---

**PRODUCT FEATURES:**

- + Premium quality 100% acrylic resin
- + High volume solids, with good opacity and film build
- + Good flow and self-leveling characteristics
- + Excellent stain and burnish resistance
- + Cleanable

---

**COLOUR:** Available in a wide range of colours. Customised colour design available.

---

### PRODUCT DESCRIPTION:

Appearance when dry: Flat finish, 2-5% sheen level at 60° tri gloss meter  
Pack size: 1L, 4L, 10L  
Theoretical coverage: 10m - 12sqm / L per coat. Apply 2 coats.  
Storage temperature: Minimum 10°C, Maximum 50°C  
Shelf life: 18 months  
V.O.C: 50g/ L (white)

---

### INTERIOR APPLICATION:

**Mixing:** Stir well using a broad paddle. Check colour before use.

**Surface preparation:** The surface must be clean, dry and free of all dust, dirt and grease. Loose flaking material must be removed and feathered back to a sound surface. Fill nail holes, cracks and blemishes with the appropriate filler or plaster compound, allow to dry and sand smooth. Patched areas must be fully cured and cleaned prior to spot priming with About Colour Gib Sealer or About Colour Alkyd Undercoat. Existing or previously painted surfaces should be washed down with a mild detergent solution and rinsed off with clean water. Any mould should be treated with a proprietary mould kill solution until completely removed and sterilized, then wash and remove all traces of chemical. Surfaces should be lightly sanded with all dust removed prior to painting. Work only when environmental conditions are within the recommended range.

**Application note:** When painting mid or deep tone colours the use of a tinted undercoat is recommended.

**New unpainted gib board, gyprock, MDF custom wood:** Refer to initial surface preparation above after all surface contaminants are removed apply 1-2 coats of About Colour Alkyd Undercoat or About Colour Gib Sealer. Lightly sand sealer with 180-200 grit sand paper to ensure an even smooth surface, clean, and then apply two coats of About Colour Matt Acrylic.

**Unpainted plaster, old unpainted gib board, gyprock, fibrous plaster, Plaster glass, timber, wallpaper:** Refer to surface preparation. After all surface contaminants are removed apply 1-2 coats of About Colour Alkyd Undercoat. Lightly sand the sealer with 180-200 grit sand paper to ensure an even smooth surface, clean, then apply two coats of About Colour Matt Acrylic.

**Surfaces previously painted with acrylic:** Refer to surface preparation. Surfaces should be lightly sanded with sanding dust removed prior to painting. Spot prime bare patches with About Colour Alkyd Undercoat or About Colour Gib Sealer then apply two coats of About Colour Matt Acrylic.

**Surfaces previously painted with enamel:**

Refer to surface preparation. Surfaces should be sanded thoroughly with sanding dust removed. Spot prime bare patches with About Colour Alkyd Undercoat. For best results then apply a full coat of About Colour Alkyd Undercoat, followed by two coats of About Colour Matt Acrylic.

**APPLICATION DETAILS:**

Application temperature range: 10°C - 35°C Note: Do not apply when air or surface temperature is likely to fall below 10°C.  
Maximum relative humidity: 75%  
Methods: Brush, roll or airless spray (2500psi, 515-619 tip)  
Thinners: Water  
Cleaning solvent: Water  
Maximum volume thinners: 5%

---

**DRYING CHARACTERISTICS:**

Temperature: 20°C  
Touch Dry: 1 Hour  
Full Cure: 24 Hours

**Over-Coating: Brush, roll:** When temperatures are above 20°C over-coating can be undertaken after two hours. For best results overnight drying is recommended. **Spray:** When using airless spray ensure overnight dry between coats

---

**ENVIRONMENTAL:** About Colour acrylic products are formulated with the latest available resins to give you both high performance and also to meet low VOC (Volatile Organic Compound) levels set out in current local standards. Likewise levels of environmentally harmful substances are either significantly reduced or eliminated.

---

**HEALTH AND SAFETY**

Special pre-cautions:

- + Keep out of reach of children.
- + This material is not to be taken internally.
- + Protect from freezing.
- + Avoid breathing vapour - use with adequate ventilation. Seal container after use.
- + Avoid contact with eyes and prolonged contact with skin.
- + Dispose of empty container carefully.
- + Do not dispose of paint in sewers or waterways.

**FIRST AID**

If swallowed:  
Eye contact:

Give water to dilute. Do not induce vomiting. Get medical attention.  
Flush with running water immediately for at least 15 minutes. Get medical attention.

This information is intended to give a fair description of the product and its capabilities under specific conditions and is correct at the time of printing. It does not constitute an offer by the manufacturers nor do they warrant or guarantee its accuracy of completeness in describing the performance or suitability of the product. The manufacturer's guarantee is only applicable to full About Colour systems and is limited to product replacement only and does not include surface preparation or application.

[www.aboutcolour.co.nz](http://www.aboutcolour.co.nz)